

T69 Self-Bunded Diesel Storage Tank

The T69 is a large-capacity, containerised self-bunded diesel storage tank designed for bulk fuel storage and high-consumption operations. Its double-wall steel construction provides integrated secondary containment, eliminating the need for external bunding while ensuring safe, environmentally compliant fuel storage.

With its extended containerised footprint and integrated pump bay configuration, the T69 is ideal for mining operations, fuel depots, logistics hubs, and large fleet refuelling environments.



Specification	T69 — Pump Bay Model
Gross Capacity	69,000 Litres
Safe Fill Capacity	65,550 Litres
Tank Type	Self Bunded (Double Wall Steel Tank)
Configuration	Containerised with integrated pump bay
Weight (Empty)	11,380 kg
Length	12,192 mm
Width	2,438 mm
Height	2,896 mm

RSA +2776 747 9075 DRC +24383 488 5299 SALES@PETROBUILD.CO.ZA

Avenue NADIA WETU, Quartier Joli Site -Cité du Park, Commune Annexe, Ville de
Lubumbashi, Province du Haut Katanga DRC

STANDARD CONSTRUCTION

- DOUBLE-WALL STEEL CONSTRUCTION
- INNER TANK THICKNESS: 5 MM
- OUTER TANK THICKNESS: 5 MM
- MANUFACTURED IN ACCORDANCE WITH UL142 / ULCS601 / AS1692 / AS1940 STANDARDS (OR EQUIVALENT)
- INDUSTRIAL-GRADE CORROSION PROTECTION COATING
- ISO CONTAINER FOOTPRINT FOR EFFICIENT TRANSPORT BY ROAD, RAIL, OR SEA

STANDARD EQUIPMENT

- LOCKABLE PUMP BAY CABINET
- ELECTRIC DIESEL TRANSFER PUMP
- FLOW METER (MECHANICAL OR DIGITAL OPTIONS AVAILABLE)
- DISPENSING HOSE WITH AUTOMATIC SHUT-OFF NOZZLE
- FILL POINT WITH CAMLOCK COUPLING
- VENT PIPE WITH WEATHERPROOF CAP
- EMERGENCY PRESSURE RELIEF VENT
- LEVEL DIPSTICK OR GAUGE
- OVERFILL PREVENTION PROVISION
- EARTHING/GROUNDING POINT
- LIFTING LUGS